

# Non-linearity and flicker noise in disordered systems

A thesis submitted in partial fulfillment for the  
degree of Doctor of Philosophy

in the  
Department of Physics  
UNIVERSITY OF CALCUTTA

by

Deep Talukdar

Saha Institute of Nuclear Physics  
1/AF, Bidhannagar, Kolkata-700064

2012

# Contents

<b>Abstract</b>	<b>i</b>
<b>Acknowledgements</b>	<b>ii</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Charge Transport in Disordered Systems . . . . .	3
1.2 Survey of different models for nonlinear conduction . . . . .	5
1.2.1 Variable range hopping under field . . . . .	7
1.2.2 Effective Temperature Model . . . . .	9
1.2.3 Multi-step tunneling . . . . .	12
1.2.4 Poole-Frenkel Effect . . . . .	14
1.3 Literature survey of non-linear conduction in different systems . . . . .	16
1.3.1 Amorphous and Doped Semiconductors . . . . .	16
1.3.2 Conducting Polymers . . . . .	19
1.3.3 Manganites . . . . .	22
1.4 $1/f$ Noise in disordered systems . . . . .	24
<b>2 Experimental methods</b>	<b>29</b>
2.1 Sample Preparation and Characterization . . . . .	29
2.1.1 Carbon Nanofiber . . . . .	29
2.1.1.1 Principle of electrospinning . . . . .	29
2.1.1.2 Carbon Nanofiber Preparation and characterization . . . . .	30
2.1.2 Conducting Polymer synthesis . . . . .	31
2.1.3 Manganites . . . . .	32
2.2 Noise Measurement Setup . . . . .	32
2.2.1 System Design: Low noise constant current source . . . . .	34
2.2.1.1 Design objectives and component choice . . . . .	34
2.2.1.2 Design, circuit, and working . . . . .	35
2.2.2 Preamplifier . . . . .	38
2.2.2.1 Motivation . . . . .	38
2.2.2.2 Design Modification . . . . .	39
2.2.3 Results . . . . .	39

2.2.4	Conclusions	44
<b>3</b>	<b>Universal scaling description of transport in disordered systems: A new Paradigm</b>	<b>45</b>
3.1	Scaling Analysis: Non-linearity exponent	47
3.2	Multi-step indirect tunneling - GM formalism	49
3.3	Illustration of the scaling approach	50
3.4	Analysis and Discussions	53
3.4.1	Non-linearity exponent: Positive vs. Negative	53
3.4.2	Non-linearity exponent: Systematics	55
3.4.3	Field Scale $F_o$ : electrically hard and Soft	59
3.4.4	Microscopic Model	60
3.4.5	An interesting Caveat	61
3.5	Non-linearity exponent: A new tool to predict transport phase transitions ?	62
3.6	Conclusions	66
<b>4</b>	<b>Unified scaling description of field dependent conductance in conducting polymers and manganites</b>	<b>67</b>
4.1	Conducting Polymers	67
4.1.1	Compatibility of the GM-expression with the scaling approach	69
4.1.1.1	Nonlinearity exponent $x_T$	71
4.1.1.2	Large bias exponent $z_T$	72
4.2	RESULTS	73
4.2.1	Polypyrrole (powder)	74
4.2.2	PEDOT (powder)	77
4.2.3	Polypyrrole (film)	80
4.2.4	Other systems in literatures	82
4.3	Discussions	86
4.3.1	Field scale $F_o$ and scaling variable	87
4.3.2	Scaling function $\Phi$	90
4.3.3	Nonlinearity exponent $x_M$	93
4.3.4	Final picture and Issues with the GM-model	96
4.4	Conclusion	99
4.5	Highly doped conducting polymer - PEDOT:PSS junctions	100
4.6	Manganites	103
4.6.1	Results and Discussions	104
<b>5</b>	<b>Flicker noise in disordered systems</b>	<b>112</b>
5.1	Experimental Results	115
5.2	Discussions	120
5.3	Conclusions	123
<b>6</b>	<b>Summary and Conclusions</b>	<b>124</b>

---

**Bibliography**

**129**